








Curtain Colours


-  5010/537
-  3000/356
-  1021/101
-  2009/205
-  7035/729



Full



Strip



Transilon

TECHNICAL DATA		A120
Door Type	Roll Up	•
Sizes	Max Width-mm	4000
	Max Height-mm	4500
Application	Internal	•
Wind class EN12424-TUV Tested	Full Curtain	Class 3
	Strip Model Curtain	Class 3
	Transilon Curtain	Class 2
Door size (mm)	Max Width	4.000
	Max Height	4.500
Working cycle	a day/24 h	350
Max door speed	m/s*optional with FU-depends on door sizes	1,5
Average door speed	Opening m/s	1
	Closing m/s	0,7
Control unit	Standard speed	•
	With frequency controller (soft start-soft stop)	o
Door frame	Galvanized steel-2 mm	o
	Stainless steel 304L V2A	•
	Powder coated paint	o
Door curtain	Spring steel wind bars with wind nuts	•
	Windnuts/Transilon Curtain	•
	Windnuts/Strip Curtain	•
Door curtain	1 mm pvc fabric	•
	2 mm clear pvc with vertical strip	o
	2 mm monofilament transilon pvc	o
	2 mm clear pvc vision panel	•
Anticrash	Aluminium Bottom profile with EPDM rubber	•
	Crash protective safety edge /WL switch	o
Manual release		Short Hand Crank
Safety devices	Photocell-Thru Beam	•
	Light curtain 2000/2500 mm	o
	Wireless bottom safety edge	o
Top cover	Galvanized steel	o
	Stainless steel	o
	Powder coated	o
Motor cover	Galvanized steel	o
	Stainless steel	o
	Powder coated	o
•:standard o:optional - :not possible		