







Curtain Colours

-  5010/537
-  3000/356
-  1021/101
-  2009/205
-  7035/729



Full

TECHNICAL DATA		D120	D120S	D140
	Fold Up	•	•	•
Sizes	Max Width-mm	5700	7500	5000
	Max Height-mm	6500	7150	5000
Application	Internal	•	•	•
	External	•	•	•
Wind class EN12424-TUV Tested	Full Curtain	Class 2	Class 2	not tested
Working cycle	a day/24 h	250	250	250
Average door speed	Opening m/s	0,7	0,7	0,7
	Closing m/s	0,7	0,7	0,7
Control unit	Standard speed	•	•	•
	Galvanized steel-2 mm	•	•	•
	Stainless steel 304L V2A	o	o	o
Door frame	Powder coated paint	o	o	o
	Aluminium modular windbars	-	-	•
	Galvanised steel pipes inside curtain	•	•	-
Door curtain	1 mm pvc fabric	•	•	-
	Modular curtain	-	-	•
	2 mm clear pvc vision panel	•	•	•
	Aluminium Bottom profile with EPDM rubber	-	-	•
	Steel weight inside pvc pocket	•	•	-
Manual release		Short Hand Crank	Short Hand Crank	Short Hand Crank
Safety devices	Photocell-Thru Beam	•	•	•
	Light curtain 2000/2500 mm	o	o	o
	Wireless bottom safety edge	o	o	o
Top cover	Galvanized steel	•	•	•
	Stainless steel	o	o	o
	Powder coated	o	o	o
Motor cover	Galvanized steel	o	o	o
	Stainless steel	o	o	o
	Powder coated	o	o	o
•:standard o:optional -:not possible				